




|                                    |   |
|------------------------------------|---|
| <b>Product Family</b>              | Gressa  |
| <b>Adjustability</b>               | Adjustable: 90°                                       |
| <b>Color</b>                       | White- Black- Gray- RAL                               |
| <b>Mounting Type</b>               |   |
| <b>Body</b>                        | Electrostatic powder coated aluminum body             |
| <b>Light Source</b>                | COB LED   |
| <b>Color Temperature</b>           | 2700-3000-4000-5000-6500K                             |
| <b>Color Rendering Index</b>       | CRI>80,CRI>90   |
| <b>Power</b>                       | 8 W   |
| <b>Power Factor</b>                | Pf>90   |
| <b>Luminaire Efficiency</b>        | 97lm/W  |
| <b>Light Beam Angle</b>            | 15°,24°,36°,60°                                       |
| <b>Lumen</b>                       | 776 lm  |
| <b>Operating Voltage</b>           | 220-240V AC / 50-60 Hz                                |
| <b>Light Source Lifetime</b>       | 50.000 hours Led lifetime                             |
| <b>Optic</b>                       | High efficiency reflector, Extra clear tempered glass |
| <b>Control Type</b>                | On/Off  |
| <b>Electrical Insulation Class</b> | Class I   |
| <b>Optional Features</b>           | Unavailable   |
| <b>Sealing</b>                     | IP66  |
| <b>Weight</b>                      | 0,6 Kg  |
| <b>Dimensions</b>                  | Ø77 x 75 x 280 mm                                     |

## DIMENSIONS



Lumen value is given according to 4000K value.  
 Luminaire is F-marked and suitable for direct mounting on normally flammable surfaces.  
 All components are provided with 5 year limited guarantee. A qualified electrician must ensure proper installation of the product.