






|                       |                                                          |
|-----------------------|----------------------------------------------------------|
| <b>Product Family</b> | Isen                                                     |
| <b>Adjustability</b>  | Fixed                                                    |
| <b>Color</b>          | White- Black- Gray- RAL                                  |
| <b>Mounting Type</b>  | Trimless                                                 |
| <b>Body</b>           | Die-cast aluminium body with electrostatic powder coated |

|                              |                                        |
|------------------------------|----------------------------------------|
| <b>Light Source</b>          | COB LED                                |
| <b>Color Temperature</b>     | 2700-3000-4000-5000-6500K              |
| <b>Color Rendering Index</b> | CRI>80,CRI>90                          |
| <b>Power</b>                 | 9 W                                    |
| <b>Power Factor</b>          | Pf>90                                  |
| <b>Luminaire Efficiency</b>  | 100lm/W                                |
| <b>Light Beam Angle</b>      | 15°,25°,38°                            |
| <b>Lumen</b>                 | 900 lm                                 |
| <b>Operating Voltage</b>     | 220-240V AC / 50-60 Hz                 |
| <b>Light Source Lifetime</b> | 50.000 hours Led lifetime              |
| <b>Optic</b>                 | High efficiency reflector and PC glass |

|                                    |                                        |
|------------------------------------|----------------------------------------|
| <b>Control Type</b>                | On/Off- Dali                           |
| <b>Electrical Insulation Class</b> | Class II                               |
| <b>Optional Features</b>           | Emergency kit system can be integrated |

|                   |              |
|-------------------|--------------|
| <b>Sealing</b>    | IP20         |
| <b>Weight</b>     | 0,55 Kg      |
| <b>Dimensions</b> | Ø84,5 x 80mm |

#### DIMENSIONS



Lumen value is given according to 4000K value.

Luminaire is F-marked and suitable for direct mounting on normally flammable surfaces.

All components are provided with 5 year limited guarantee. A qualified electrician must ensure proper installation of the product.