




|                                    |  |
|------------------------------------|--|
| <b>Product Family</b>              | Lunet  |
| <b>Adjustability</b>               | Fixed  |
| <b>Color</b>                       |  |
| <b>Mounting Type</b>               | Pendant  |
| <b>Body</b>                        | External frame   |
| <b>Light Source</b>                | MP LED   |
| <b>Color Temperature</b>           | 2500K  |
| <b>Color Rendering Index</b>       | CRI>80 , CRI>90  |
| <b>Power</b>                       | 55 W/m <sup>2</sup>  |
| <b>Power Factor</b>                | Pf>90  |
| <b>Luminaire Efficiency</b>        | 35lm/W   |
| <b>Light Beam Angle</b>            | 110°   |
| <b>Lumen</b>                       | 1925 lm  |
| <b>Operating Voltage</b>           | 220-240V AC / 50-60 Hz   |
| <b>Light Source Lifetime</b>       | 50.000 hours Led lifetime  |
| <b>Optic</b>                       | Stretch ceiling fabric   |
| <b>Control Type</b>                | On/Off   |
| <b>Electrical Insulation Class</b> | Class I  |
| <b>Optional Features</b>           | Unavailable  |
| <b>Sealing</b>                     | IP40   |
| <b>Weight</b>                      |  |
| <b>Dimensions</b>                  | It can be manufactured in desired dimensions according to the project. |

#### DIMENSIONS



Projeye göre istenilen ölçülerde imal edilebilir.  
It can be manufactured in desired dimensions according to the project.

Lumen value is given according to 2500K value.

Luminaire is F-marked and suitable for direct mounting on normally flammable surfaces.

All components are provided with 5 year limited guarantee. A qualified electrician must ensure proper installation of the product.