


| | |
|-----------------------|----------------------------|
| Product Family | Luro |
| Adjustability | Fixed |
| Color | White- Black- Gray- RAL |
| Mounting Type | Pendant |
| Body | Extruded aluminum heatsink |

| | |
|------------------------------|----------------------------------------|
| Light Source | MP LED |
| Color Temperature | 2700-3000-4000-5000-6500K |
| Color Rendering Index | CRI>80,CRI>90 |
| Power | 30 W |
| Power Factor | Pf>90 |
| Luminaire Efficiency | 97lm/W |
| Light Beam Angle | 120° |
| Lumen | 2910 lm |
| Operating Voltage | 220-240V AC / 50-60 Hz |
| Light Source Lifetime | 50.000 hours Led lifetime |
| Optic | High efficiency polycarbonate diffuser |

| | |
|------------------------------------|-------------|
| Control Type | On/Off |
| Electrical Insulation Class | Class II |
| Optional Features | Unavailable |

| | |
|-------------------|-------------------|
| Sealing | IP40 |
| Weight | 1,3 Kg |
| Dimensions | Ø40 x L : 1350 mm |

DIMENSIONS



Lumen value is given according to 4000K value.

Luminaire is F-marked and suitable for direct mounting on normally flammable surfaces.

All components are provided with 5 year limited guarantee. A qualified electrician must ensure proper installation of the product.