




| | |
|------------------------------------|--|
| Product Family | Onda |
| Adjustability | Fixed |
| Color | MAT Eloksal |
| Mounting Type | |
| Body | Extruded aluminium body with electrostatic powder coated |
| Light Source | MP LED |
| Color Temperature | 2700-3000-4000-5000-6500K |
| Color Rendering Index | CRI>80 , CRI>90 |
| Power | 145 W |
| Power Factor | Pf>90 |
| Luminaire Efficiency | 136lm/W |
| Light Beam Angle | 30°,60°,90° |
| Lumen | 19720 lm |
| Operating Voltage | 220-240V AC / 50-60 Hz |
| Light Source Lifetime | 50.000 hours Led lifetime |
| Optic | High efficiency reflector and extra clear tempered glass |
| Control Type | On/Off |
| Electrical Insulation Class | Class I |
| Optional Features | Emergency kit system can be integrated |
| Sealing | IP65 |
| Weight | 7,1 Kg |
| Dimensions | 150 X 70 L: 560 mm |

DIMENSIONS



Lumen value is given according to 5000K value.

Luminaire is F-marked and suitable for direct mounting on normally flammable surfaces.

All components are provided with 5 year limited guarantee. A qualified electrician must ensure proper installation of the product.