




Product Family	Rell
Adjustability	Fixed
Color	MAT Eloksal
Mounting Type	Trimless
Body	Extruded aluminium body
Light Source	MP LED
Color Temperature	2700-3000-4000-5000-6500K
Color Rendering Index	CRI>80, CRI>90
Power	14 W/Mt
Power Factor	Pf>90
Luminaire Efficiency	20 lm/W
Light Beam Angle	120°
Lumen	280 lm/mt
Operating Voltage	220-240V AC / 50-60 Hz
Light Source Lifetime	50.000 hours Led lifetime
Optic	High efficiency extruded silicon
Control Type	On/Off
Electrical Insulation Class	Class III
Optional Features	Unavailable
Sealing	IP65
Weight	2,6 Kg
Dimensions	50 x 34 x XX mm

DIMENSIONS




CONNECTION CONFIGURATIONS/ BAĞLANTI KONFIGURASYONLARI


If you have more than one product, use extra power source every 10 meters. Connect the leds in parallel to the power supply every 10 meters.
Connect both ends of the LED to the power supply.

Birten fazla ürününüz varsa her 10 metrede bir ekstra güç kaynağı kullanın. Ledleri her 10 metrede bir güce paralel olarak bağlayın. Ledlerin her iki ucunu da güce kaynağına bağlayın.

CONNECTION TYPE 1 BAĞLANTI TİPİ 1 İP65 YA DA İP65 BLAT KULLUĞU İP65 OR İP65 JUNCTION BOX (PROVIDE CORE QUALITY AND CONTROL IT WILL BE EVALUATED ACCORDING TO THE PROJECT)



CONNECTION TYPE 2 BAĞLANTI TİPİ 2



CONNECTION TYPE 3 BAĞLANTI TİPİ 3



BAĞLANTI KABLOLARI PROFİL İÇİNDEN GEÇERKEN BAĞLANTI KABLOLARI PROFİL İÇİNDEN GEÇERKEN CONNECTION CABLES WILL PASS THROUGH THE PROFILE

Lumen value is given according to 3000K value.

Luminaire is F-marked and suitable for direct mounting on normally flammable surfaces.

All components are provided with 5 year limited guarantee. A qualified electrician must ensure proper installation of the product.