


| | |
|------------------------------------|--|
| Product Family | Sova |
| Adjustability | Fixed |
| Color | White- Black- Gray- RAL |
| Mounting Type | Recessed Mounted |
| Body | Extruded aluminium body with electrostatic powder coated, electrostatic powder coated sheet metal side cover |
| Light Source | HP LED |
| Color Temperature | 2700-3000-4000-5000-6500K |
| Color Rendering Index | CRI>80 |
| Power | 6,8 W |
| Power Factor | Pf>90 |
| Luminaire Efficiency | 92lm/W |
| Light Beam Angle | 10°,25°,40°,60° |
| Lumen | 626 lm |
| Operating Voltage | 220-240V AC / 50-60 Hz |
| Light Source Lifetime | 50.000 hours Led lifetime |
| Optic | High efficiency acrylic lens |
| Control Type | On/Off- Dali |
| Electrical Insulation Class | Class I |
| Optional Features | Emergency kit system can be integrated |
| Sealing | IP20 |
| Weight | 0,43 Kg |
| Dimensions | 223 x 51,7 x 54 mm |

DIMENSIONS



Lumen value is given according to 2700K value.

Luminaire is F-marked and suitable for direct mounting on normally flammable surfaces.

All components are provided with 5 year limited guarantee. A qualified electrician must ensure proper installation of the product.