



|                                    |  |
|------------------------------------|--|
| <b>Product Family</b>              | Tivra  |
| <b>Adjustability</b>               | Fixed  |
| <b>Color</b>                       | White- Black- Gray- RAL                                  |
| <b>Mounting Type</b>               | Recessed Mounted   |
| <b>Body</b>                        | Extruded aluminium body with electrostatic powder coated |
| <b>Light Source</b>                | COB LED  |
| <b>Color Temperature</b>           | 2700-3000-4000-5000-6500K                                |
| <b>Color Rendering Index</b>       | CRI>80, CRI>90   |
| <b>Power</b>                       | 4x14 W   |
| <b>Power Factor</b>                | Pf>90  |
| <b>Luminaire Efficiency</b>        | 103lm/W  |
| <b>Light Beam Angle</b>            | 15°, 24°, 36°, 60°                                       |
| <b>Lumen</b>                       | 5768 lm  |
| <b>Operating Voltage</b>           | 220-240V AC / 50-60 Hz                                   |
| <b>Light Source Lifetime</b>       | 50.000 hours Led lifetime                                |
| <b>Optic</b>                       | High efficiency reflector and PC glass                   |
| <b>Control Type</b>                | On/Off   |
| <b>Electrical Insulation Class</b> | Class I  |
| <b>Optional Features</b>           | Unavailable  |
| <b>Sealing</b>                     | IP20   |
| <b>Weight</b>                      | 5,6 KG   |
| <b>Dimensions</b>                  | 120 x 78 x 1500 mm                                       |

### DIMENSIONS



Lumen value is given according to 4000K value.

Luminaire is F-marked and suitable for direct mounting on normally flammable surfaces.

All components are provided with 5 year limited guarantee. A qualified electrician must ensure proper installation of the product.