


<b>Product Family</b>	Viora
<b>Adjustability</b>	Fixed
<b>Color</b>	White- Black- Gray- RAL
<b>Mounting Type</b>	Pendant
<b>Body</b>	Extruded aluminium body with electrostatic powder coated

<b>Light Source</b>	HP LED
<b>Color Temperature</b>	2700-3000-4000-5000-6500K
<b>Color Rendering Index</b>	CRI>80
<b>Power</b>	25 W
<b>Power Factor</b>	Pf>90
<b>Luminaire Efficiency</b>	120 lm/W
<b>Light Beam Angle</b>	12°,36°,48°,10X35°
<b>Lumen</b>	3000 lm
<b>Operating Voltage</b>	220-240V AC / 50-60 Hz
<b>Light Source Lifetime</b>	50.000 hours Led lifetime
<b>Optic</b>	High efficiency optic in metallized thermoplastic and built into the innovative anti-glare screen

<b>Control Type</b>	On/Off
<b>Electrical Insulation Class</b>	Class I
<b>Optional Features</b>	Emergency kit system can be integrated

<b>Sealing</b>	IP20
<b>Weight</b>	1,8 Kg
<b>Dimensions</b>	33 x 72 x L : 1120 mm

#### DIMENSIONS



Lumen value is given according to 3000K value.

Luminaire is F-marked and suitable for direct mounting on normally flammable surfaces.

All components are provided with 5 year limited guarantee. A qualified electrician must ensure proper installation of the product.